

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (original): Correcting device to compensate for perturbations of the polarization distribution over the cross section of a light beam (10) in an optical system (56), having at least one correcting component (18; 118) which comprises a birefringent correcting element (22; 122; 222; 322) having two essentially parallel surfaces (26; 126, 127), between which the thickness (d) of the correcting element (22; 122, 222) is essentially constant,

characterized in that

the at least one correcting component (18, 118) comprises at least one further birefringent correcting element (20; 120a, 120b; 220; 320), which is assigned to the first correcting element (22; 122; 222; 322) and has two essentially parallel surfaces (24), in that at least one of the surfaces (24, 26; 126, 127) of at least one of the correcting elements (20, 22; 120a, 120b, 122; 220; 222; 320, 322) is reprocessed so as to create local thickness variations  $\Delta d$  by which the perturbations of the polarization distribution are compensated for at least approximately, and in that the arrangement, thickness (d) and birefringence properties of the correcting elements (20, 22; 120a, 120b, 122; 220; 222; 320, 322) are selected so that their birefringent effects cancel each other out when the local thickness variations  $\Delta d$  are neglected.

PRELIMINARY AMENDMENT

Attorney Docket No.: Q92234

Page 4

2. (original): Correcting device according to Claim 1, characterized in that the correcting elements (20, 22; 120a, 120b, 122; 220; 222; 320, 322) consist of the same material.

3. (original): Correcting device according to Claim 2, characterized in that the surfaces (24, 26; 126, 127) of the correcting elements (20, 22; 120a, 120b, 122; 220; 222; 320, 322) are reprocessed complementarily with one another so that the total thickness ( $d_g$ ) of all the correcting elements (20, 22; 120a, 120b, 122; 220; 222; 320, 322) of a correcting component (18; 118) is constant over its cross section.

4. (original): Correcting device according to Claim 3, characterized in that the correcting component (18; 118) comprises two correcting elements, and in that the local thickness variation  $\Delta d$  required for the perturbation compensation at a particular point is distributed so that the thickness ( $d$ ) of one correcting element (22) is reduced by  $\Delta d/2$  at this point, and that of the other correcting element (20) is increased by  $\Delta d/2$ .

5. (currently amended): Correcting device according to ~~one of the preceding claims~~ Claim 1, characterized in that the surfaces of the correcting elements (320, 322) are curved.

6. (currently amended): Correcting device according to ~~one of the preceding claims~~ Claim 1, characterized in that the correcting component (18, 118) comprises two correcting

PRELIMINARY AMENDMENT

Attorney Docket No.: Q92234

Page 5

elements (20, 22; 120a, 120b, 122; 220; 222; 320, 322) whose birefringence axes are mutually rotated by  $90^\circ$ .

7. (currently amended): Correcting device according to ~~one of the preceding claims~~ Claim 1, characterized in that at least one correcting element (220) has a surface which is additionally reprocessed (40) so as to reduce wavefront errors due to the thickness variations.

8. (currently amended): Correcting device according to ~~one of the preceding claims~~ Claim 1, characterized in that two correcting components (18, 220 and 222) are provided, the birefringence axes of the correcting elements (20, 22) of one correcting component (18) being rotated by  $45^\circ$  relative to the birefringence axes of the correcting elements (220, 222) of the other correcting component.

9. (currently amended): Projection objective for microlithography, having a correcting device (316) according to ~~one of the preceding claims~~ Claim 1.

10. (original): Projection objective according to Claim 9, characterized in that the correcting device (316) is arranged at least approximately in a pupil plane (72) of the projection objective (56).

11. (original): Projection objective according to Claim 10, characterized in that the correcting device (316) is arranged in the immediate vicinity of an imaging mirror (68), which is

PRELIMINARY AMENDMENT

Attorney Docket No.: Q92234

Page 6

contained in a catadioptric part of the projection objective (56).

12. (currently amended): Projection objective ~~according to Claim 10 or 11~~ for microlithography, comprising a correcting device (316) according to Claim 1 and arranged at least approximately in a pupil plane (72) of the projection objective (56), characterized in that and further comprising a further correcting device according to one of Claims 1 to 8 is Claim 1 arranged at least approximately in a field plane of the projection objective (56).

13. (new): Projection objective for microlithography, comprising a correcting device (316) according to Claim 1 and arranged in the immediate vicinity of an imaging mirror (68), which is contained in a catadioptric part of the projection objective (56), and further comprising a further correcting device according to Claim 1 arranged at least approximately in a field plane of the projection objective (56).